



The ankerbolt is a grade 8.8 self tapping anchor for use in a variety of base materials. The self tapping action provides a positive anchorage in concrete, brick, stone and blocks. The ankerbolt performs well in both solid and hollow materials.

Hexagon Flange Head • Zinc Plated and Clear Passivated

Part Number	Drill Diameter mm	Anchor Length mm	Maximum Fixture Thickness mm	Minimum Hole Depth mm	Driver Type	Quantity Per Box	Ship Weight Kg Per 100	Price £ Per 100
JAB06050	5.0	50	20	40	8mm A/F	100	0.98	16.81
JAB06075	5.0	75	45	40	8mm A/F	100	1.35	19.47
JAB08030	6.0	30	5	35	10mm A/F	100	1.00	24.44
JAB08050	6.0	50	20	40	10mm A/F	100	1.49	25.21
JAB08075	6.0	75	45	40	10mm A/F	100	2.02	32.45
JAB08100	6.0	100	55	45	10mm A/F	100	2.57	38.55
JAB08130	6.0	130	85	45	10mm A/F	100	3.23	45.82
JAB08150	6.0	150	105	45	10mm A/F	100	3.66	50.08



Hexagon Head • Zinc Plated and Clear Passivated

Part Number	Drill Diameter mm	Anchor Length mm	Maximum Fixture Thickness mm	Minimum Hole Depth mm	Driver Type	Quantity Per Box	Ship Weight Kg Per 100	Price £ Per 100
JAB10060	8.0	60	20	55	15mm A/F	100	2.99	31.12
JAB10075	8.0	75	35	55	15mm A/F	100	3.58	37.61
JAB10100	8.0	100	60	55	15mm A/F	100	4.53	52.25
JAB10150	8.0	150	110	55	15mm A/F	50	5.48	80.47
JAB12060	10.0	60	10	70	17mm A/F	50	4.68	48.63
JAB12075	10.0	75	25	70	17mm A/F	50	5.50	54.29
JAB12100	10.0	100	50	70	17mm A/F	50	7.06	70.62
JAB12150	10.0	150	100	70	17mm A/F	25	10.15	108.93
JAB14075	12.0	75	15	85	19mm A/F	50	8.00	73.58
JAB14100	12.0	100	40	85	19mm A/F	50	10.18	91.89
JAB14130	12.0	130	70	85	19mm A/F	25	12.75	118.20
JAB14150	12.0	150	90	85	19mm A/F	20	14.17	190.53
JAB14200	12.0	200	140	85	19mm A/F	20	18.90	251.04
JAB18100	16.0	100	20	112	27mm A/F	10	22.00	308.06
JAB18150	16.0	150	70	112	27mm A/F	10	29.70	359.21
JAB18200	16.0	200	120	112	27mm A/F	10	37.60	436.01