



### Countersunk • Zinc Plated and Clear Passivated

Part Number	Drill Diameter mm	Anchor Length mm	Max. Fixture Thickness mm	Minimum Hole Depth mm	Head Diameter mm	Driver Type	Quantity Per Box	Ship Weight Kg Per 100	Price £ Per 100
JAB08050CS	6.0	50	20	40	12.5	T30 Torx	100	1.19	20.04
JAB08075CS	6.0	75	45	40	12.5	T30 Torx	100	1.73	25.21
JAB08100CS	6.0	100	55	55	12.5	T30 Torx	100	2.58	31.57
JAB08130CS	6.0	130	85	55	12.5	T30 Torx	100	2.94	40.57
JAB08150CS	6.0	150	105	55	12.5	T30 Torx	100	3.32	46.43



### Hook Bolt and Eye Hook • Zinc Plated and yellow Passivated

Part Number	Drill Diameter mm	Anchor Length mm	Maximum Fixture Thickness mm	Minimum Hole Depth mm	Hook/Eye Diameter mm	Quantity Per Box	Ship Weight Kg Per 100	Price £ Per 100
JAB08050HOOK	6.0	90	N/A	40	12	50	2.56	98.64
JAB10055HOOK	8.0	90	N/A	45	12	50	4.96	110.76
JAB08050EYE	6.0	90	N/A	40	13	50	2.80	153.78
JAB10055EYE	8.0	90	N/A	45	13	50	5.50	182.21

### T30 Torx Driver Bit

Part Number	Quantity	Price £ Each
T30	1	1.99

### Technical Information C20/25 Concrete

Anchor Diameter mm	Drill Diameter mm	Embedment Depth mm	Fixture Clearance Hole mm	Centre Spacing mm	Edge Distance mm	Structure Thickness mm	Rec. Tensile Load KN	Rec. Shear Load KN	Rec. Tightening Torque Nm
6	5	30	7	90	45	50	1.0	3.3	15
8	6	30 (25)	10	100	50	60	1.9 (0.8)	3.6(0.8)	25 (15)
10	8	40	12	120	60	70	2.9	8.6	40
12	10	50	14	170	80	90	4.4	14.3	60
14	12	60	16	200	90	110	6.3	19.3	80
18	16	80	20	260	120	140	8.6	24.3	100

Shear loads are for loads away from a free edge

(Figures in brackets are for JAB0830 Only)