



A torque controlled shield anchor suitable for use in concrete and solid brickwork.

Loose Bolt • Zinc Plated and Yellow Passivated (8.8 Bolt) • Min 5µm

Part Number	Thread Diameter	Shield Hole Size mm	Maximum Fixture Thickness mm	Length Under Head mm	Minimum Hole Depth mm	Quantity Per Box/Outer	Ship Wt. Kg Per 100	Price £ Per 100
ALB0610	M6	12	10	55	50	50/600	2.36	84.10
ALB0625	M6	12	25	70	50	50/600	2.80	102.35
ALB0640	M6	12	40	85	50	50/600	3.20	105.32
ALB0810	M8	14	10	60	55	50/450	5.78	115.24
ALB0825	M8	14	25	75	55	50/300	6.20	126.39
ALB0840	M8	14	40	90	55	50/300	6.46	143.54
ALB1010	M10	16	10	70	65	50/200	9.44	166.96
ALB1025	M10	16	25	85	65	50/200	9.96	197.36
ALB1050	M10	16	50	110	65	50/200	11.14	215.32
ALB1075	M10	16	75	135	65	25/150	12.90	235.67
ALB1210	M12	20	10	85	85	25/150	17.84	263.69
ALB1225	M12	20	25	100	85	25/100	18.40	311.31
ALB1240	M12	20	40	115	85	25/100	19.16	347.94
ALB1260	M12	20	60	135	85	25/100	21.28	379.15
ALB1615	M16	25	15	135	125	10/50	36.30	705.46
ALB1630	M16	25	30	150	125	10/50	36.60	754.05
ALB1660	M16	25	60	180	125	10/50	42.40	906.12



Eye Bolts (Forged Eye) • Zinc Plated and Yellow Passivated • Min 5µm

Part No.	Thread Diameter	Shield Hole Size mm	Eye Diameter mm	Overall Length mm	Rec. Tensile Load kN	Quantity Per Box	Ship Wt. Kg Per 100	Price £ Per 100
AEBM06	M6	12	10	80	1.4	25	7.96	137.88
AEBM08	M8	14	11	95	2.6	25	8.52	181.69
AEBM10	M10	16	14	115	4.2	10	15.62	246.54
AEBM12	M12	20	16	130	6.1	10	27.64	470.56



Hook Bolts (Forged Hook) • Zinc Plated and Yellow Passivated • Min 5µm

Part No.	Thread Diameter	Shield Hole Size mm	Eye Diameter mm	Overall Length mm	Rec. Tensile Load kN	Quantity Per Box	Ship Wt. Kg Per 100	Price £ Per 100
AHBM06	M6	12	8	80	0.8	25	7.60	137.88
AHBM08	M8	14	10	95	1.6	25	8.20	181.69
AHBM10	M10	16	12	115	2.5	10	14.50	246.54
AHBM12	M12	20	16	145	3.9	10	26.90	470.56