

Frame Fixings



A nylon plug with a zinc plated screw for fixing into concrete or masonry

Nylon Frame Fixing • Drive Screw Zinc Plated and Yellow Passivated

Part Number	Anchor Hole Size mm	Anchor Plug Length mm	Max. Fixture Thickness mm	Minimum Hole Depth mm	Rec. Tensile Load KN	Rec. Shear Load KN	Quantity Per Box/Outer	Ship Wt. Kg Per 100	Price £ Per 100
NFF08060	8	60	20	45	1.0	1.5	100/1000	1.24	25.11
NFF08080	8	80	40	45	1.0	1.5	100/1000	1.56	28.35
NFF08100	8	100	60	45	1.0	1.5	100/1000	1.70	31.74
NFF08120	8	120	80	45	1.0	1.5	100/1000	1.89	41.75
NFF10080	10	80	35	50	1.3	2.0	100/1000	2.40	42.82
NFF10100	10	100	55	50	1.3	2.0	100/1000	3.44	44.98
NFF10120	10	120	75	50	1.3	2.0	100/1000	3.80	53.39
NFF10140	10	140	95	50	1.3	2.0	100/1000	4.36	61.62
NFF10160	10	160	115	50	1.3	2.0	100/1000	5.16	81.71

C20/25 Concrete



Window Frame Anchor • For use with PVC Frames

Part Number	Anchor Hole Size mm	Anchor Plug Length mm	Max. Fixture Thickness mm	Minimum Hole Depth mm	Rec. Tensile Load KN	Rec. Shear Load KN	Quantity Per Box/Outer	Ship Wt. Kg Per 100	Price £ Per 100
NWFA08100	8	100	50	55	0.8	1.0	50/1000	1.63	30.81
NWFA08120	8	120	70	55	0.8	1.0	50/1000	1.98	36.43
NWFA08140	8	140	90	55	0.8	1.0	50/1000	2.34	41.79
NWFA10080	10	80	25	65	1.3	1.5	50/1000	1.84	37.06
NWFA10100	10	100	50	65	1.3	1.5	50/1000	2.39	38.80
NWFA10120	10	120	70	65	1.3	1.5	50/800	2.93	43.67
NWFA10140	10	140	90	65	1.3	1.5	50/800	3.49	54.49
NWFA10165	10	165	115	65	1.3	1.5	50/600	4.12	68.61

Concrete Screws



A countersunk self tapping screw, zinc plated and yellow passivated, suitable for use in concrete, concrete blocks and masonry.
A T30 drive bit supplied in each box

Concrete Screw • Includes White Cover Cap

Part Number	Drill Diameter mm	Screw Length mm	Max. Fixture Thickness mm	Minimum Hole Depth mm	Rec. Tensile Load KN	Rec. Shear Load KN	Quantity Per Box	Ship Wt. Kg Per 100	Price £ Per 100
CS75040	6	40	-	45	2.0	2.5	100	1.00	16.27
CS75060	6	60	20	45	2.0	2.5	100	1.45	18.60
CS75080	6	80	40	45	2.0	2.5	100	1.72	24.40
CS75100	6	100	60	45	2.0	2.5	100	2.53	27.12
CS75120	6	120	80	45	2.0	2.5	100	2.93	37.18
CS75150	6	150	110	45	2.0	2.5	100	3.16	44.93
CS75180	6	180	140	45	2.0	2.5	100	3.78	82.89

T30 Torx Driver Bit

T30							1		1.99
-----	--	--	--	--	--	--	---	--	------

C20/25 Concrete