

A thin walled sleeve anchor suitable for use in most types of concrete or masonry.



Sleeve Anchor • Hexagon Nut • Stainless Steel A4-316

Part Number	Anchor Hole Size mm	Anchor Length mm	Maximum Fixture Thickness mm	Minimum Hole Depth mm	Quantity Per Box/Outer	Ship Wt. Kg Per 100	Price £ Per 100
SLSS06060	6	60	25	35	100/1000	1.26	114.48
SLSS08040	8	40	8	40	100/1000	2.31	128.55
SLSS08065	8	65	30	40	50/500	2.48	158.90
SLSS10050	10	50	8	45	50/500	3.28	200.66
SLSS10075	10	75	35	45	50/500	4.62	259.22
SLSS10100	10	100	60	45	50/400	5.88	326.14
SLSS12060	12	60	10	50	50/300	5.81	333.60
SLSS12075	12	75	22	60	50/300	6.88	374.88
SLSS12100	12	100	45	60	25/250	9.05	472.88

Technical Information C20/25 Concrete

Anchor Hole Size mm	Thread Diameter mm	Embedment Depth mm	Fixture Clearance Hole mm	Centre Spacing mm	Edge Distance mm	Structure Thickness mm	Rec. Tensile Load KN	Rec. Shear Load KN	Rec. Tightening Torque Nm
6	M4.5	30	7-8	80	40	50	1.8	1.6	10
8	M6	35	9-10	90	45	60	2.2	1.8	20
10	M8	40	11-12	100	50	70	3.4	3.3	40
12	M10	50	13-14	130	65	90	4.2	5.3	65

Shear loads are for loads away from a free edge

Scaffold Ring Bolts

Scaffolding ring bolts are used together with M16 drop in anchors or M16 internal threaded sockets for restraining scaffolding



Part Number	Thread Diameter mm	Eye Diameter mm	Overall Length mm	Quantity Per Box	Ship Wt. Kg Each	Price £ Each
DSRBM16	16	53	210	1/25	0.6	10.85

Forged Hooks & Eyes

Forged Hook and Eyebolts • Zinc Plated and Clear Passivated • Min 5µm

Hook Bolts



Part Number	Thread Diameter mm	Thread Length mm	Eye Diameter mm	Quantity Per Box	Price £ Per 100
FHM06	6	50	8.0	50	73.50
FHM08	8	60	10.0	50	114.63
FHM10	10	73	12.0	25	181.75
FHM12	12	90	16.0	10	371.93

Eye Bolts



Part Number	Thread Diameter mm	Thread Length mm	Eye Diameter mm	Quantity Per Box	Price £ Per 100
FEM06	6	50	10.0	50	77.18
FEM08	8	60	11.0	50	120.36
FEM10	10	73	14.0	25	190.83
FEM12	12	90	16.0	10	389.94